3K STRAP HOIST

⚠ WARNING

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



KEY FEATURES

- ASME B-30-21 compliant
- 125% working load tested
- Hi-viz green strap
- Interlocking pawl lever system
- Replacement parts readily available
- Hot stick operable version

Use the Slingco 3k Strap Hoist to splice, dead end, and sag lines. The Slingco 3k Strap Hoist features an interlocking pawl lever system with dual pawl springs for controlled tightening and releasing of the strap and to ensure the hoist is engaged while in use. The strap hoist complies with ASME B-30-21 standard and all units are tested to 125% of load.

The Slingco 3k Strap Hoist uses pressure die castings for a professional look, consistent material properties, and smooth finish. The strap is hi-viz bright green in color for easy visibility. The strap hoist has three operating positions: lift/pull, lower/release, and freewheeling.

Slingco Part No.	Type	Single Line Capacity lb (kg)	Single Line Lift ft (m)	Single Line Headroom in (mm)	Double Line Capacity lb (kg)	Double Line Lift ft (m)	Double Line Headroom in (mm)	Tool Weight lb (kg)
ZLH10504	Standard	1,500 (680)	10 (3)	17.5 (444.5)	3,000 (1,360)	5 (1.5)	22 (558.8)	11.25 (5.1)
ZLH10524	Hot stick operated	1,500 (680)	10 (3)	17.5 (444.5)	3,000 (1,360)	5 (1.5)	22 (558.8)	11.5 (5.22)

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG **t:** 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA **t:** 888 685 9478

GET IN TOUCH

01706 855 558
sales@slingco.com

3K STRAP HOIST

Part Number	Description	Pack quantity	For ZLH10504	For ZLH10524
ZLH13609	Drum Casting	Pack of 1	X	X
ZLH13611	Polyester Web	Pack of 1	X	X
ZLH13614	Holding Pawl Casting	Pack of 10	X	
ZLH13926	ZLH13926	Pack of 10		X
ZLH13615	Holding Pawl Shaft	Pack of 1	X	
ZLH13919	Holding Pawl Shaft	Pack of 1		X
ZLH13608	Nylon Wheel	Pack of 1	X	X
ZLH13610	Drum Shaft	Pack of 1	X	X
ZLH13745	Torsion Spring	Pack of 10	X	X
ZLH13620	Ø 0.125" X 1.25" Roll Pin	Pack of 20	X	X
ZLH13621	Ø 0.125" X 1.5" Roll Pin	Pack of 20	X	X
ZLH13591	Main Frame Assembly	Pack of 1	X	
ZLH13920	Main Frame Assembly	Pack of 1		X
ZLH13560	Hook With Latch	Pack of 1	X	
ZLH13921	Hook With Latch	Pack of 1		X
ZLH13562	Eye Bolt	Pack of 1	X	X
ZLH13616	Main Frame Roller	Pack of 1	X	X
ZLH13618	Ø 0.25" X 2" Roll Pin	Pack of 20	X	X
ZLH13622	9/16"-12 Hex Slotted Nut	Pack of 10	X	X
ZLH13619	Ø 0.125" X 0.875" Roll Pin	Pack of 20	X	X
ZLH13593	Idler Roller Assembly	Pack of 1	X	
ZLH13927	Idler Roller Assembly	Pack of 1		X
ZLH13599	Yoke Casting	Pack of 1	X	X
ZLH13597	Yoke Roller Shaft	Pack of 1	X	X
ZLH13598	Yoke Roller	Pack of 1	X	X
ZLH13561	Latch Spares Kit	Pack of 10	X	X
ZLH13617	Steel Retaining Ring	Pack of 20	X	X
ZLH13596	Handle Assembly	Pack of 1	X	
ZLH13929	Handle Assembly	Pack of 1		X
ZLH13595	Control Casting Assembly	Pack of 10	X	X
ZLH13594	Swivel Shackle Assembly	Pack of 1	X	
ZLH13928	Swivel Shackle Assembly	Pack of 1		X
ZLH13592	U-Frame Assembly	Pack of 1	X	
ZLH13922	U-Frame Assembly	Pack of 1		X
ZLH13563	Loading Pawl Casting	Pack of 10	X	
ZLH13924	Loading Pawl Casting	Pack of 10		X
ZLH13564	Loading Pawl Shaft	Pack of 1	X	
ZLH13925	Loading Pawl Shaft	Pack of 1		X
ZLH13565	Reversing Spring	Pack of 10	X	X
ZLH13566	Control Lever	Pack of 10	X	
ZLH13923	Control Lever	Pack of 10		X
ZLH13612	U-Frame Casting	Pack of 1	X	X
ZLH13613	Handle Locking Screw	Pack of 10	X	X
ZLH13918	Hot Stick Lever	Pack of 1		X

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions
The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG **t:** 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA **t:** 888 685 9478

GET IN TOUCH
01706 855 558
sales@slingco.com

3K STRAP HOIST

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG **t:** 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA **t:** 888 685 9478

GET IN TOUCH
01706 855 558
sales@slingco.com