



Part Number	ZGC12033	ZGC12034
Size	1.66"	1.66"
Style	Duckbill	Duckbill
Clamp Material	Aluminum	Aluminum
Eyscrew Material	Bronze	Bronze
Screw Style	ACME	ACME
Screw Grip	Eye	Eye
Jaw Style	Serrated	Serrated
Ferrule Type	Threaded	Threaded
Main Line Rane	1.66"-0.16" 42.16 mm - 4.06 mm	1.66""-0.16" 42.16 mm - 4.06 mm
Strain Relief Sleeve	No	Yes
Weight	1.85 lb / 0.84 kg	1.98 lb / 0.90 kg
Grade	5/5H	5/5H
Class	B	B
Continuous Current (RMS), 60Hz	400	400
Fault Current - 15 Cycles (AMPS)	47,000 (Grade 5H) 43,000 (Grade 5)	47,000 (Grade 5H) 43,000 (Grade 5)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)

**Slingco America, Inc.**  
130 Celtic Blvd, Tyrone,  
Georgia, 30290, USA  
TOLL FREE: 888 685 9478  
sales@slingcoamerica.com

**Slingco Limited**  
Gateway Business Park, New Hall Hey Road,  
Rawtenstall, BB4 6JG, England  
Tel: +44 [0]1706 855558  
sales@slingco.com

**Slingco Australia Pty. Ltd.**  
L9, 1 York Street, Sydney,  
NSW 2000, Australia  
Sales: +61 3 8840 6556  
sales@slingcoaustralia.com.au

**888-685-9478**

**+44 [0]1706 855558**

**+61 3 8840 6556**

**slingco.com**

Grounding Clamps Specification Sheet - ZGC12033-12034 March 2026

Slingco makes no warranty, express or implied, with respect to this product nor with respect to its specifications. In no event shall Slingco be liable for any direct, indirect, punitive, incidental, special consequential damages to property or life, whatsoever, arising out of or connected with the use or misuse of this product. This product is intended for use by qualified professionals having adequate knowledge of its proper use. March 2026 - v1.0