



Part Number	ZGC12037	ZGC12038
Size	2.00"	2.00"
Style	C-Clamp	C-Clamp
Clamp Material	Aluminum	Aluminum
Eyscrew Material	Bronze	Bronze
Screw Style	ACME	ACME
Screw Grip	Eye	Eye
Jaw Style	Serrated	Smooth
Ferrule Type	Threaded	Threaded
Main Line Rane	2.00" - 0.16" 50.80 mm - 4.06 mm	2.00" - 0.16" 50.80 mm - 4.06 mm
Strain Relief Sleeve	No	No
Weight	2.25 lb / 1.02 kg	2.20 lb / 1.00 kg
Grade	5/5H	5/5H
Class	B	A
Continuous Current (RMS), 60Hz	400	400
Fault Current - 15 Cycles (AMPS)	47,000 (Grade 5H) 43,000 (Grade 5)	47,000 (Grade 5H) 43,000 (Grade 5)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)

Slingco America, Inc.
130 Celtic Blvd, Tyrone,
Georgia, 30290, USA
TOLL FREE: 888 685 9478
sales@slingcoamerica.com

Slingco Limited
Gateway Business Park, New Hall Hey Road,
Rawtenstall, BB4 6JG, England
Tel: +44 [0]1706 855558
sales@slingco.com

Slingco Australia Pty. Ltd.
L9, 1 York Street, Sydney,
NSW 2000, Australia
Sales: +61 3 8840 6556
sales@slingcoaustralia.com.au

888-685-9478

+44 [0]1706 855558

+61 3 8840 6556

slingco.com

Grounding Clamps Specification Sheet - ZGC12037-12038 March 2026

Slingco makes no warranty, express or implied, with respect to this product nor with respect to its specifications. In no event shall Slingco be liable for any direct, indirect, punitive, incidental, special consequential damages to property or life, whatsoever, arising out of or connected with the use or misuse of this product. This product is intended for use by qualified professionals having adequate knowledge of its proper use. March 2026 - v1.0