

OFFSET EYE SPLIT MESH LACE CLOSING SUPPORT GRIPS



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Supports cable in vertical or horizontal mode
- ✓ Use when the end of the cable is not accessible

This grip, in 304 Stainless Steel, is ideal for several support points along the same cable when the cable ends are not accessible.

Slingco Part No.	Approx. Break Load (lb)	Approx. Break Load (kg)	Lattice Length (in)	Lattice Length (mm)	Range (in)	Range (mm)
ZCS1926	500	225	10	254	0.50 - 0.63	12 - 16
ZCS1927	750	340	10	254	0.63 - 0.75	16 - 19
ZCS1928	950	430	13	330	0.75 - 1.00	19 - 25
ZCS1929	1,500	680	14	355	1.00 - 1.25	25 - 31
ZCS1930	1,500	680	15	381	1.25 - 1.50	31 - 38
ZCS1931	1,500	680	17	432	1.50 - 1.75	38 - 44
ZCS1932	2,000	905	19	482	1.75 - 2.00	44 - 50
ZCS1933	2,150	975	21	533	2.00 - 2.50	50 - 63
ZCS1934	2,150	975	23	584	2.50 - 3.00	63 - 76
ZCS1935	3,800	1,720	25	635	3.00 - 3.50	76 - 89
ZCS1936	3,800	1,720	27	685	3.50 - 4.00	89 - 102

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



GET IN TOUCH

1 888 685 9478

sales@slingcoamerica.com